

2105 S

TECHNICAL SPECIFICATIONS

MODEL	4WD		
ENGINE			
Engine Type	1104D-44TA		
Emission Type	Stage 3A		
Aspiration	Turbo / Intercooler		
Cubic Capacit/ Number of Cylinders (cm ³ /Number)	4400 / 4		
Max. Engine Power (ISO 14396) (kw/hp/rpm)	75 / 102 / 2200		
Max Torque (Nm/rpm)	416 / 1400		
Engine Cooling System	Water Cooled		
Fuel Capacity (lt)	120		
TRANSMISSION			
Gearbox Type	Mechanical Synchromesh		
Shuttle (Synchronizer)	Standart		
Number of Speeds	24 + 24		
Creeper	Standart		
Max.-Min Speed (km/h)	0,48 - 40		
4WD Actuation	Electro Hydraulic		
Front Differential Lock System	Limited Slip		
Rear Differential Lock System	Electro Hydraulic		
HYDRAULIC SYSTEM			
Functions	Position - Power - Mixed		
Hydraulic Power (Output Valves)	6		
Lifting Capacity (kg)	3400		
POWER TAKE OFF			
Type	Independent Four Speed		
Ground Speed Pto	Standart		
PTO Debriyajı	Electro Hydraulic		
Pto	430 - 540 - 540E -1000		
Pto (rpm)	2073 - 1881 - 1530 - 2048		
BRAKES			
Type	Oil Bath Disc Brake		
Foot Brake	Hydraulic Controlled		
Hand Brake	Mechanically Controled		
TYRES			
1. Option (Front)	340/85 R24		
1. Option (Rear)	460/85 R30		
2. Option (Front)	340/85 R24		
2. Option (Rear)	420/85 R34		
3. Option (Front)	340/85 R24		
3. Option (Rear)	340/85 R38		
DIMENSIONS (mm)			
Length	4355		
Height	2783		2807
Wheelbase	2445		
Track Width (Front) (mm)	1392		1843
Track Width (Rear) (mm)	1386		1900
Ground Clearence	355		
WEIGHTS (kg)			
Front Weights	8 x 30 + 50		
Rear Weights	6 x 45		
Total Weight (Without Ballasts)	3900		
ACCESSORIES			
Ledbar	Standart		
Compressor	Standart		
Hydraulic Middle Arm	Standart		
Rear Cam And Display	Optional		